

# PERFECT DRY



**Macchina a rullo per l'applicazione di graniglie e polveri**

*Roller machine for the application of grits and powders*



**La macchina consente di creare «venature» di prodotto, ed altri effetti sulle piastrelle**

*The machine allows to make product «veining» and other effects on tiles*



CONTROLLO PESO  
WEIGHT CONTROL



ALTA PRODUZIONE  
HIGH PRODUCTION

## DESCRIZIONE TECNICA TECHNICAL DESCRIPTION

Caratteristica principale della macchina è la semplicità d'uso, la perfetta stesura anche con polveri molto fini e pochissimi grammi di prodotto, fino a coperture con quantità elevate. Il sistema è composto da un serbatoio/elevatore, un serbatoio/rullo per la distribuzione sulla piastrella e da un nastro per il recupero del prodotto in eccesso.

La zona di stesura è completamente chiusa per ridurre al minimo le fuoriuscite di polveri, ed è provvista di lampade ad infrarossi e resistenze elettriche per eliminare l'umidità delle polveri. La macchina è comandata da pannello di controllo, completo di touch-screen, che permette di regolare tutti i parametri di lavorazione e di salvarli in ricette.

Ciclone per aspirazione graniglie in eccesso dalla superficie della piastrella.

Completo di sistema per il convogliamento della graniglia aspirata, nella tramoggia principale della macchina di applicazione graniglie. Il ciclone di aspirazione polveri, unito alla macchina Perfect Dry, consente di creare «venature» di prodotto, ed altri effetti sulle piastrelle.

*The machine consents a big range of application, from very low grams of grits to big quantity. The system is composed of a tank/elevator, tank/roller for the distribution on the tile and a conveyor belt for excess product recovery.*

*The application area is completely closed in order to reduce the product leak to its lowest and it is provided with infrared lamps and intake plugs in order to eliminate humidity from powders.*

*The machine is controlled by an electric panel with a touch-screen that allows to adjust all working parameters and save them into formulas.*

*Cyclone for excess grits aspiration from tiles surfaces. It is provided with a system for conveying aspirated grits to the main hopper of the machine.*

*The powders aspiration cyclone, together with Perfect Dry machine, allows to make product «veining» and other effects on tiles.*



T.G. MAC SRL  
VIA SAN GIACINTO 2/4  
41042 FIORANO MODENESE (MO)  
TEL. +39 0536 805596  
FAX. +39 0536 804891  
INFO@TGMAC.IT  
WWW.TGMAC.IT  
P.I. 01295850364

